

40 mm Carbo



Swivel blocks can lock in two directions or swivel



2638



2639



2640



2641



2642



2643



2647



2648



2654



Use with 2619 for a powerful 8:1 purchase



2655



2656



2657



2658



Actual Size

| Part No. | Description | Sheave Ø | | Length | | Weight w/shackle | | Shackle pin Ø | | Max line Ø | | Maximum working load | | Breaking load | |
|----------|---------------------------------------|--------------------------------|----|---------------------------------|-----|------------------|-----|--------------------------------|----|-------------------------------|----|----------------------|-----|---------------|------|
| | | in | mm | in | mm | oz | g | in | mm | in | mm | lb | kg | lb | kg |
| 2638 | Double/swivel | 1 ⁹ / ₁₆ | 40 | 3 ¹¹ / ₁₆ | 94 | 3.2 | 86 | 3 ⁹ / ₁₆ | 5 | 3 ⁷ / ₈ | 10 | 970 | 440 | 2380 | 1080 |
| 2639 | Double/swivel/becket | 1 ⁹ / ₁₆ | 40 | 4 ⁵ / ₁₆ | 110 | 3.4 | 90 | 3 ⁹ / ₁₆ | 5 | 3 ⁷ / ₈ | 10 | 970 | 440 | 2380 | 1080 |
| 2640 | Triple/swivel | 1 ⁹ / ₁₆ | 40 | 3 ¹¹ / ₁₆ | 94 | 4.6 | 118 | 3 ⁹ / ₁₆ | 5 | 3 ⁷ / ₈ | 10 | 1455 | 660 | 3050 | 1383 |
| 2641 | Triple/swivel/becket | 1 ⁹ / ₁₆ | 40 | 4 ⁵ / ₁₆ | 110 | 4.7 | 122 | 3 ⁹ / ₁₆ | 5 | 3 ⁷ / ₈ | 10 | 1455 | 660 | 3050 | 1383 |
| 2642 | Double/fixed | 1 ⁹ / ₁₆ | 40 | 3 ¹ / ₂ | 89 | 2.8 | 80 | 3 ⁹ / ₁₆ | 5 | 3 ⁷ / ₈ | 10 | 970 | 440 | 2380 | 1080 |
| 2643 | Double/fixed/becket | 1 ⁹ / ₁₆ | 40 | 4 ³ / ₁₆ | 106 | 2.9 | 84 | 3 ⁹ / ₁₆ | 5 | 3 ⁷ / ₈ | 10 | 970 | 440 | 2380 | 1080 |
| 2647 | Triple/swivel/423 Carbo-Cam®** | 1 ⁹ / ₁₆ | 40 | 3 ¹¹ / ₁₆ | 94 | 8.2 | 232 | 3 ⁹ / ₁₆ | 5 | 1 ¹ / ₄ | 6 | 750 | 340 | 1500 | 680 |
| 2648 | Triple/swivel/423 Carbo-Cam®/becket** | 1 ⁹ / ₁₆ | 40 | 4 ⁵ / ₁₆ | 110 | 8.3 | 235 | 3 ⁹ / ₁₆ | 5 | 1 ¹ / ₄ | 6 | 900 | 408 | 1800 | 816 |
| 2654 | Quad/swivel | 1 ⁹ / ₁₆ | 40 | 3 ¹¹ / ₁₆ | 94 | 6 | 170 | 3 ⁹ / ₁₆ | 5 | 3 ⁷ / ₈ | 10 | 1455 | 660 | 3050 | 1383 |
| 2655 | Fiddle | 1 ⁹ / ₁₆ | 40 | 4 ¹ / ₂ | 115 | 1.8 | 51 | 5 ³ / ₃₂ | 4 | 3 ⁷ / ₈ | 10 | 485 | 220 | 1620 | 735 |
| 2656 | Fiddle/becket | 1 ⁹ / ₁₆ | 40 | 5 ¹ / ₈ | 131 | 1.9 | 54 | 5 ³ / ₃₂ | 4 | 3 ⁷ / ₈ | 10 | 485 | 220 | 1620 | 735 |
| 2657 | Fiddle/423 Carbo-Cam® | 1 ⁹ / ₁₆ | 40 | 4 ¹ / ₂ | 115 | 4.4 | 125 | 5 ³ / ₃₂ | 4 | 1 ¹ / ₄ | 6 | 485 | 220 | 1620 | 735 |
| 2658 | Fiddle/423 Carbo-Cam®/becket | 1 ⁹ / ₁₆ | 40 | 5 ¹ / ₈ | 131 | 4.5 | 128 | 5 ³ / ₃₂ | 4 | 1 ¹ / ₄ | 6 | 485 | 220 | 1620 | 735 |

**Maximum working loads and breaking loads for blocks based on cam strengths