

# 57 mm & 75 mm Carbo



Swivel blocks can lock in two directions or swivel



Hobie 16, 2008 European Championships  
— Pierrick Contin photo



Use with 2632 for a powerful 8:1 purchase

Part No.	Description	Sheave Ø		Length		Weight w/shackle		Shackle pin Ø		Max line Ø		Maximum working load		Breaking load	
		in	mm	in	mm	oz	g	in	mm	in	mm	lb	kg	lb	kg
<b>57 mm</b>															
2602	Double/swivel	2 <sup>1</sup> / <sub>4</sub>	57	4 <sup>3</sup> / <sub>4</sub>	121	6.3	178	—	6	7 <sup>1</sup> / <sub>16</sub>	10	1584	720	3300	1500
2603	Double/swivel/becket	2 <sup>1</sup> / <sub>4</sub>	57	5 <sup>5</sup> / <sub>8</sub>	142	6.6	187	—	6	7 <sup>1</sup> / <sub>16</sub>	10	1584	720	3300	1500
2604	Triple/swivel	2 <sup>1</sup> / <sub>4</sub>	57	4 <sup>3</sup> / <sub>4</sub>	121	9	255	—	6	7 <sup>1</sup> / <sub>16</sub>	10	2380	1080	5000	2270
2605	Triple/swivel/becket	2 <sup>1</sup> / <sub>4</sub>	57	5 <sup>5</sup> / <sub>8</sub>	142	9.3	264	—	6	7 <sup>1</sup> / <sub>16</sub>	10	2380	1080	5000	2270
2617	Triple/swivel/150 Cam-Matic®**	2 <sup>1</sup> / <sub>4</sub>	57	4 <sup>3</sup> / <sub>4</sub>	121	15.2	431	—	6	7 <sup>1</sup> / <sub>16</sub>	10	1500	680	3750	1700
2618	Triple/swivel/150 Cam-Matic®/becket**	2 <sup>1</sup> / <sub>4</sub>	57	5 <sup>5</sup> / <sub>8</sub>	142	15.6	442	—	6	7 <sup>1</sup> / <sub>16</sub>	10	1800	816	4500	2040
2631	Quadruple/swivel	2 <sup>1</sup> / <sub>4</sub>	57	4 <sup>3</sup> / <sub>4</sub>	121	12	340	—	6	7 <sup>1</sup> / <sub>16</sub>	10	2380	1080	5000	2270
<b>75 mm</b>															
2662	Double/swivel	2 <sup>15</sup> / <sub>16</sub>	75	6	152	14.2	402	5 <sup>9</sup> / <sub>16</sub>	8	9 <sup>9</sup> / <sub>16</sub>	14	2426	1100	6000	2722
2663	Double/swivel/becket	2 <sup>15</sup> / <sub>16</sub>	75	7	178	14.8	419	5 <sup>9</sup> / <sub>16</sub>	8	9 <sup>9</sup> / <sub>16</sub>	14	2426	1100	6000	2722
2664	Triple/swivel	2 <sup>15</sup> / <sub>16</sub>	75	6	152	20.5	580	5 <sup>9</sup> / <sub>16</sub>	8	9 <sup>9</sup> / <sub>16</sub>	14	3639	1650	10000	4535
2665	Triple/swivel/becket	2 <sup>15</sup> / <sub>16</sub>	75	7	178	21.1	599	5 <sup>9</sup> / <sub>16</sub>	8	9 <sup>9</sup> / <sub>16</sub>	14	3639	1650	10000	4535
2668	Triple/swivel/150 Cam-Matic®**	2 <sup>15</sup> / <sub>16</sub>	75	6	152	27.8	788	5 <sup>9</sup> / <sub>16</sub>	8	1 <sup>1</sup> / <sub>2</sub>	12	1500	680	3750	1700
2669	Triple/swivel/150 Cam-Matic®/becket**	2 <sup>15</sup> / <sub>16</sub>	75	7	178	28.4	805	5 <sup>9</sup> / <sub>16</sub>	8	1 <sup>1</sup> / <sub>2</sub>	12	1800	816	4500	2040
2677	Quadruple/swivel	2 <sup>15</sup> / <sub>16</sub>	75	6 <sup>1</sup> / <sub>4</sub>	159	27.2	772	5 <sup>9</sup> / <sub>16</sub>	8	9 <sup>9</sup> / <sub>16</sub>	14	3639	1650	10000	4535

\*\*Maximum working loads and breaking loads for blocks based on cam strengths