

2.25 in & 3.00 in

The 2.25 in (57 mm) and 3.00 (76 mm) are compact and lightweight, with fast trim and release under high or low loads. Perfect for dinghies, scows, beachcats and iceboats, as well as small offshore racers and cruisers.

Delrin® ball bearings, sheave, and sideplates are UV stabilized with carbon black for maximum protection.

The 3.00 in (76 mm) single block comes in high-load or low-load configurations. High-load blocks feature Torlon® bearings and forged stainless steel shackles.

The wire version features Hardkote-anodized, Teflon®-impregnated aluminum sheaves for strength and corrosion resistance.

Use for:

- Main and jib sheets
- Spinnaker halyards
- Control lines

Shackle can lock in either direction or can swivel to keep line from twisting

High-strength stainless steel straps reinforce blocks

Multiple sheave configurations use a bridge coupler to spread the load

Removable becket allow attachment of spliced line



US Olympic 2.4 m, John Ruf — Walter Cooper photo



Part No.	Description	Sheave Ø		Length		Weight		Max line Ø		Shackle pin Ø		Maximum working load		Breaking load	
		in	mm	in	mm	oz	g	in	mm	in	mm	lb	kg	lb	kg
2.25"															
001	Single	2 1/4	57	4 1/4	108	4 1/2	128	7/16	12	3/16	5	500	227	2500	1134
002	Single/becket	2 1/4	57	5	127	5	142	7/16	12	3/16	5	500	227	2500	1134
003	Double	2 1/4	57	4 1/2	114	8 1/2	241	7/16	12	1/4	6	1000	454	3000	1361
004	Double/becket	2 1/4	57	5 1/2	138	9 1/2	269	7/16	12	1/4	6	1000	454	3000	1361
013	Cheek†*	2 1/4	57	3 1/4	83	5	142	7/16	12	—	—	500	227	2500	1134
047	Thru-deck*	2 1/4	57	3 1/2	89	5	156	7/16	12	—	—	500	227	2500	1134
076	Triple/becket	2 1/4	57	5 3/4	146	13 1/2	383	7/16	12	1/4	6	1200	544	3000	1361
206	Upright lead**	2 1/4	57	3 1/4	83	5 1/2	156	7/16	12	—	—	500	227	2500	1134
3.00"															
005	Single	3	76	5	127	7	198	7/16	12	3/16	5	750	340	2500	1134
011	Heavy-duty single	3	76	5 1/4	133	8	227	7/16	12	1/4	6	750	340	3000	1361
012	Heavy-duty single/becket	3	76	6 1/4	159	8 1/2	241	7/16	12	1/4	6	750	340	3000	1361
202	Wire single	3	76	5 1/4	133	9 1/2	269	7/16	12	1/4	6	850	386	3000	1361

†Includes fasteners & mounting pad *#8 (4 mm) RH fasteners **#10 (5 mm) RH fasteners