

57 mm

Black Magic®

NEW: 3195

Use 57 mm Black Magic® AirBlocks® on offshore boats. These strong, lightweight blocks are sculpted aluminum, with Torton® rollers and carbon-black balls for strength and UV protection. Rollers are housed in a unique center cage and are isolated for less friction. Blocks feature a three-way head system for less friction. Blocks feature a three-way head system and come in high- and low-load configurations.

The 3195 soft attachment Loop block has a removable dead-end post for attachment to a padeye. Lashings can also be used.

Use for:

- Sheets
- Halyards
- Running backstays
- Control lines

Three-way head system—shackle can lock in either direction or can swivel to keep line from twisting

Headpost rides on plastic bushing

Three fasteners for quick disassembly

Torton® roller bearings for strength and reduced wear

Easy to open integrated becket

Low-load blocks have red isolators



1951
1959



Sly 42, Studio Lostuzzi Yacht Design & Engineering, Sly Yachts — Sly Yachts photo

See page 96

Part No.	Description	Sheave Ø		Length		Weight w/shackle		Shackle pin Ø		Max Line Ø		Maximum working load		Breaking load	
		mm	in	mm	in	oz	g	in	mm	in	mm	lb	kg	lb	kg
1950	Single/swivel/low-load	57	4 ¹ / ₁₆	119	5.0	142	1/4	6	7/16	12	1655	750	3310	1500	
1951	Single/swivel/low-load/becket	57	5 ¹ / ₂	140	5.5	155	1/4	6	7/16	12	1655	750	3310	1500	
1952	Double/swivel/low-load	57	5 ³ / ₁₆	132	10.1	286	5/16	8	7/16	12	2755	1250	5510	2500	
1954	Triple/swivel	57	5 ³ / ₁₆	132	13.2	375	5/16	8	7/16	12	4850	2200	9700	4400	
1958	Single/swivel/high-load	57	4 ¹ / ₁₆	119	5.0	142	1/4	6	7/16	12	2500	1134	5000	2268	
1959	Single/swivel/high-load/becket	57	5 ¹ / ₂	140	5.5	155	1/4	6	7/16	12	2500	1134	5000	2268	
1960	Double/swivel/high-load	57	5 ³ / ₁₆	132	10.1	286	5/16	8	7/16	12	3600	1633	7200	3267	
1961	Double/swivel/high-load/becket	57	6	152	10.6	302	5/16	8	7/16	12	3600	1633	7200	3267	
1965	Stand-up/high-load*	57	4 ¹ / ₂	114	7.4	210	1/4	6	7/16	12	2500	1134	5000	2268	
3195	Single loop block	57	3	76	3.25**	92**	—	—	7/16	12	2500	1134	5000	2268	

*1/4" (6 mm)—Fastener circle: 1¹/₂" (37 mm) **Weight without loop