

Mastbase Halyard Lead

Low-profile mastbase halyard lead blocks are lightweight and can be grouped in a small area at the mastbase. Flared cheeks prevent chafe on the halyards.

Keeps line close to deck

High-load bearing system has Teflon® composite bushing, sideload balls

Hardkote-anodized aluminum sheave for additional strength



1986



1988
1990
3123
C8508

Part No.	Description	Sheave Ø		Width		Length		Height		Max line Ø		Weight		Maximum working load		Breaking load	
		in	mm	in	mm	in	mm	in	mm	in	mm	oz	g	lb	kg	lb	kg
1986	Halyard lead block*	1 ³ / ₄	44	7 ⁷ / ₈	22	3 ¹³ / ₁₆	97	2 ¹ / ₄	57	3 ³ / ₈	10	3.36	95	750	340	1500	680
1988	Mastbase block/fixe**	2 ¹ / ₄	57	1 ³ / ₈	35	3 ¹³ / ₁₆	81	2 ¹ / ₈	73	3 ³ / ₈	10	6.2	175	2500	1136	5000	2273
1990	Mastbase block/fixe***	3	76	1 ⁵ / ₈	41	4 ⁵ / ₈	117	3 ³ / ₄	95	1 ¹ / ₂	12	11.5	326	5000	2273	10000	4545
3123	Mastbase block/fixe‡	4	102	1 ⁵ / ₈	41	5 ¹ / ₈	130	5 ¹ / ₈	130	1 ¹¹ / ₁₆	18	24.9	708	11000	4990	22000	9980
C8508	Mastbase block/fixe‡‡	4 ¹⁵ / ₁₆	125	1 ¹⁵ / ₁₆	49	7 ¹ / ₄	184	6 ⁷ / ₃₂	158	3 ³ / ₄	19	44.5	1261	15000	6804	30000	13608

*1/4" (6 mm) RH **3/4" (6 mm) FH ***5/16" (8 mm) FH ‡5/8" 16 mm HH ‡‡Contact Harken to request quote and lead time. For full product line, visit www.harkencustom.com

Over-the-Top

Over-the-top blocks lead lines aft over cabin houses, coamings, and splashguards. They feature high-load sheaves and come in single, double, and triple configurations.

C8322
3002
C8624



3003

3004

Part No.	Description	Sheave Ø		Width		Length		Height		Max line Ø		Weight		Maximum working load		Breaking load	
		in	mm	in	mm	in	mm	in	mm	in	mm	oz	g	lb	kg	lb	kg
3002	Single over-the-top block*	2 ¹ / ₄	57	1 ³ / ₈	35	3 ¹ / ₄	83	3 ¹ / ₄	83	3 ³ / ₈	10	6.4	181	2500	1136	5000	2272
3003	Double over-the-top block*	2 ¹ / ₄	57	2 ¹ / ₁₆	62	3 ¹ / ₄	83	3 ¹ / ₄	83	3 ³ / ₈	10	12.2	346	2500	1136	5000	2272
3004	Triple over-the-top block*	2 ¹ / ₄	57	3 ¹ / ₂	89	3 ¹ / ₄	83	3 ¹ / ₄	83	3 ³ / ₈	10	18.1	513	2500	1136	5000	2272
C8322	Single over-the-top block**	1 ³ / ₄	45	1 ¹ / ₁₆	36	3 ¹ / ₁₆	78	3 ⁷ / ₃₂	82	1 ¹ / ₂	12	5.6	159	2500	1136	5000	2272
C8624	Single over-the-top block**	2 ¹⁵ / ₁₆	75	1 ¹¹ / ₁₆	43	4	101	4	101	3 ³ / ₁₆	14	18.5	526	5000	2272	10000	4536

*1/4" (6 mm) FH **Contact Harken to request quote and lead time. For full product line, visit www.harkencustom.com

Flip-Flop

The low-profile Flip-Flop blocks are light weight and can be used for various leads on your boat including halyard leads, mainsheet leads and spinnaker sheet leads.

The Flip-Flop block has aluminum Hardkote-anodized side plates and features Hardkote-anodized Teflon impregnated aluminum sheaves for strength and corrosion resistance.

The high-load flip-flop blocks pivot around the line axis to keep line close to the deck. Hinged construction allows variable leads. Lockoff provides a temporary stop to free up winches.

Hollow axle runs line close to deck

High-load bearing system has Teflon® composite bushing, sideload balls



3194
1989



3122
1987

Block mounts on machined aluminum feet. Pivots easily on plastic isolators

Part No.	Description	Sheave Ø		Width		Length		Height		Max line Ø		Weight		Maximum working load		Breaking load	
		in	mm	in	mm	in	mm	in	mm	in	mm	oz	g	lb	kg	lb	kg
1987	Flip-flop block*	3	76	2 ¹ / ₈	72	6	152	4	100	1 ¹ / ₂	12	17.37	493	5000	2273	10000	4545
1989	Flip-flop block/lockoff*	3	76	2 ¹ / ₈	72	6	152	4	100	1 ¹ / ₂	12	21.1	598	5000	2273	10000	4545
3122	Flip-flop block**	2 ¹ / ₄	57	2 ¹ / ₄	57	4 ³ / ₈	111	2 ¹ / ₈	73	3 ³ / ₈	10	9	255	2500	1136	5000	2273
3194	Flip-flop block/lockoff**	2 ¹ / ₄	57	2 ¹ / ₄	57	4 ³ / ₈	111	2 ¹ / ₈	73	3 ³ / ₈	10	11.2	317.8	2500	1136	5000	2273

5/16" (8 mm) SH *1/4" (6 mm) SH