

Snatch Blocks

Harken® Snatch blocks feature low-friction roller/ball bearing sheaves and a unique push-button latch for one-handed operation. The opening side allows sheets to be inserted without reeving.

Urethane sideplates prevent damage to decks, spars, and cabin houses. An integral bail allows blocks to hang from lifelines with shockcord. Snap shackles attach to padeyes and bails, while trunnion shackles attach to toerails and other fixtures.

Snatch blocks are offered in high-load and low-load configurations and are used on offshore boats of all sizes.

Use for:


- Genoa leads
- Mast base reefing blocks
- Protected trip buttons
- Changing sheets
- Spinnaker sheet deflector blocks



High-load

Snap/trunnion shackle

One-handed latch



1608



1601



1600

Part No.	Description	Sheave Ø		Length		Weight		Max line Ø		A		B		Maximum working load		Breaking load	
		in	mm	in	mm	oz	g	in	mm	in	mm	in	mm	lb	kg	lb	kg
1600	Snatch block	2 1/2	64	5 3/4	146	18	510	5/8	16	5/8	16	3/4	19	2250	1021	4500	2041
1601	High-load	2 1/2	64	6 1/4	159	19	552	5/8	16	5/8	16	11/16	26	3500	1588	7000	3175
1608	Midrange/trunnion	2 1/2	64	5 13/16	147	18	510	5/8	16	11/16	17	13/16	21	2250	1021	4500	2041
1609	Midrange/high-load/trunnion	2 1/2	64	5 9/16	166	20	564	5/8	16	7/8	22	11/16	26	3500	1588	7000	3175

High-Load Snatch Blocks

Crew can quickly fasten these opening blocks wherever needed. ULC bearing technology ensures sheaves turn smoothly and maintain efficiency at high loads. Snap-fit Torton® ball bearings handle thrust loads, and the integral head-spacer prevents the Hardkote-anodized sideplates from binding the sheave. The articulating Loop carries the block's primary load.

Use for:

Static line applications

Sideplate pivots around the sheave axis, making it easy to attach to rigged line



Strong, lightweight Velcro® strap holds block closed when sideplates are aligned



HC8796
HC8832



HC8910
HC8628

Part No.	Description	Sheave Ø		Length		Weight*		Loop Ø		Max line Ø		Maximum working load		Breaking load		Use Loop
		in	mm	in	mm	oz	g	in	mm	in	mm	lb	kg	lb	kg	
HC8796	2.3T Snatch block	1 1/2	38.5	2 3/8	60	3.95	112	5/16	7	7/16	11	5070	2300	10140	4600	HCP1800
HC8832	5T Snatch block	2 1/4	56	2 3/8	86	8.64	245	3/8	10	5/8	16	10805	5000	21610	9800	HCP1772
HC8910	8T Snatch block	3	75	4 1/2	114	20.28	575	1/2	12	3/4	18	18080	8000	36160	16400	HCP1868
HC8628	12T Snatch block	4	100	5 13/16	148	47.62	1350	11/16	17	1 3/16	30	26460	12000	52920	24000	HCP1852

Contact Harken to request quote and lead time. For full product line, visit www.harkencustom.com *Includes weight of Loop and Velcro® strap