

Cruising ESP

Set screw in three-way head locks shackle in front or side positions, or lets block swivel to keep line from twisting



6059
6058
6100



6094
6084



6085



6086



6099

Elan 410, Rob Humphreys, Elan Marine — Val Nautika photo

Part No.	Description	Sheave Ø		Length		Weight		Shackle pin Ø		Max line Ø		Maximum working load		Breaking load	
		in	mm	in	mm	oz	g	in	mm	in	mm	lb	kg	lb	kg
57 mm															
6059	Single/swivel	2¼	57	5½	140	7.7	218	⅝	8	⅝	16	2500	1135	5000	2272
6094	Single/swivel/becket	2¼	57	6⅛	170	9	255	⅝	8	⅝	16	2500	1135	5000	2272
75 mm															
6058	Single/swivel	3	75	6¼	159	12	340	⅝	8	¾	19	3500	1587	7000	3175
6084	Single/swivel/becket	3	75	7¼	184	13	369	⅝	8	¾	19	3500	1587	7000	3175
6085	Fiddle	3/1⅜	75/46	8⅜	213	14.7	415	⅝	8	¾	19	3500	1587	7000	3175
6086	Fiddle/becket	3/1⅜	75/46	9½	241	15.6	444	⅝	8	¾	19	3500	1587	7000	3175
6099	Fiddle/becket/280 Cam-Matic®	3/1⅜	75/46	9½	241	25.2	715	⅝	8	¾	19	2000	907	4000	1814
100 mm															
6100	Single/swivel	4	100	8⅞	206	28.5	808	⅞	10	¾	19	4870	2209	9740	4418