

Stainless Steel Cruising ESP



Part No.	Description	Sheave Ø		Length		Weight		Clevis/Shackle pin Ø		Max line Ø		Maximum working load		Breaking load‡		Max lockoff load		Fasteners (RH)	
		in	mm	in	mm	oz	g	in	mm	in	mm	lb	kg	lb	kg	lb	kg	in	mm
57 mm																			
6068	Single/swivel	2 1/4	57	5 1/2	140	11	312	5/16	8	5/8	16	2500	1135	5000	2272	—	—	—	—
6069	Mastcollar	2 1/4	57	3 11/16	93.5	7	198	5/16	8	5/8	16	2500	1135	5000	2272	—	—	—	—
6070	Single foot/lockoff* ‡	2 1/4	57	3 3/4	132	9	255	—	—	5/8	16	2500	1135	5000	2272	650	295	3/8	10
6076	Footblock* ** ‡	2 1/4	57	3 3/4	95	7	198	—	—	5/8	16	2500	1135	5000	2272	—	—	3/8	10
6089	Single/swivel/becket	2 1/4	57	6 11/16	170	12.5	354	5/16	8	5/8	16	2500	1135	5000	2272	—	—	—	—
75 mm																			
6072	Single/swivel	3	75	6 1/4	159	19	539	5/16	8	3/4	19	3500	1587	7000	3175	—	—	—	—
6073	Mastcollar	3	75	4 5/8	117	16	454	5/16	8	3/4	19	3000	1361	6000	2721	—	—	—	—
6074	Single foot/lockoff* ‡	3	75	4 3/8	111	17	482	—	—	3/4	19	3500	1587	7000	3175	750	340	3/8	10
6079	Footblock* ** ‡	3	75	4 1/2	114	16	454	—	—	3/4	19	3500	1587	7000	3175	—	—	3/8	10
6080	Fiddle	3 1 13/16	75/46	8 3/8	213	24	680	5/16	8	3/4	19	3500	1587	7000	3175	—	—	—	—
6081	Fiddle/becket	3 1 13/16	75/46	9 1/2	241	26.25	744	5/16	8	3/4	19	3500	1587	7000	3175	—	—	—	—
6087	Single/swivel/becket	3	75	7 1/4	184	21.25	602	5/16	8	3/4	19	3500	1587	7000	3175	—	—	—	—
Deck Organizers																			
6071	Deck organizer/3-sheave‡	2 1/4	57	9 5/16	252	21	595	—	—	5/8	16	6000	2721	12000	5442	—	—	3/8	10
6075	Deck organizer/3-sheave‡	1 1/2	40	7 11/16	179	10	284	—	—	1/2	12	3000	1361	6000	2721	—	—	5/16	8

*Lockoffs are intended to hold lines temporarily and should not be used in place of line stoppers or clutches **Refer to page 74 for 6076/6079 hole spacing ‡If double stacked, upper block/organizer is two-thirds of listed MWL and breaking load