

Grand Prix

TTR Blocks

The TTR (Titanium Roller) AirBlock® surpasses all other blocks with 98% efficiency, increasing trimming speed and harnessing power other blocks lose to friction. 6061-T6 Hardkote-anodized Teflon®-impregnated sideplates don't flex, so sheaves run smoothly. High-load titanium rollers handle bearing loads. Snap-fit Torton® ball bearings carry side loads.

ULC Loop Blocks

ULC (Ultra Light Composite) blocks feature lightweight, strong materials and Harken's standard bearing system for an exceptionally high strength-to-weight ratio. ULC blocks excel in static line applications that require small adjustments.

Articulating Loop attachments and sculpted head ensure a fair lead

C8734

Soft attachment Loops carry the primary load for a lightweight block

Inner and outer bearing races are made of titanium for strength

Block opens easily for maintenance



Soft attachment Loops can be configured as becket or fiddle block



Numbers, Judd/Vrolijk 66', Goetz Custom Boats
— Sharon Green photo



C8488



C8878



C8580

Part No.	Description	Sheave Ø		Length		Weight		Max line Ø		Maximum working load		Breaking load	
		in	mm	in	mm	oz	g	in	mm	lb	kg	lb	kg
ULC Loop*													
C7915	40 mm Tall wide	1 ⁹ / ₁₆	40	2.95	75	5.36	152	2 x 1/2	2 x 12	5100	2313	10201	4626
C8291	40 mm Short wide	1 ⁹ / ₁₆	40	2.44	62	5.19	147	2 x 1/2	2 x 12	5100	2313	10201	4626
C8488	40 mm Short narrow	1 ⁹ / ₁₆	40	2.40	61	3.88	110	1/2	12	5100	2313	10201	4626
TTR**													
C8878	3.0T AirBlock®	2.24	57	2.79	71	3.84	109	3/8	10	6614	3000	13228	6000
C8491	5.0T Narrow AirBlock®	3	75	3.82	97	7.77	220	1/2	12	11025	5000	22050	10000
C8580	5.0T Wide AirBlock®	3	75	3.82	97	9.32	264	2 x 1/2	2 x 12	11025	5000	22050	10000
C8723	5.0T Narrow footblock	3	75	4.29	109	16.16	458	9/16	14	11025	5000	22050	10000
C8724	5.0T Wide footblock	3	75	4.68	119	17.6	499	2 x 9/16	2 x 14	11025	5000	22050	10000
C8727	5.0T Sheave	3	75	—	—	6.56	186	9/16	14	11025	5000	22050	10000
C8575	6.5T Narrow AirBlock®	4	100	4.92	125	16.03	454	5/8	16	14333	6500	28666	13000
C9161	6.5T Wide AirBlock®	4	100	5.79	147	22.4	635	2 x 3/4	2 x 20	14333	6500	28666	13000
C9015	6.5T Sheave	4	100	—	—	14.1	400	3/4	20	14333	6500	28666	13000
C8462	8.0T Narrow AirBlock®	5	125	6.06	154	29.48	835	1 ¹ / ₁₆	18	17641	8000	35281	16000
C8757	8.0T Wide AirBlock®	5	125	5.94	151	34.39	975	2 x 5/8	2 x 16	17641	8000	35281	16000
C8807	8.0T Footblock	5	125	6.49	165	48.78	1383	3/4	19	17641	8000	35281	16000
C8754	10.0T Narrow AirBlock®	6	150	7.1	181	48.29	1368	9/16	20	22046	10000	44092	20000
C8957	10.0T Wide AirBlock®	6.1	155	7.67	195	72.77	2063	2 x 7/8	2 x 22	22046	10000	44092	20000
C8755	12.0T AirBlock®	7	175	8.3	221	66.86	1894	7/8	22	26455	12000	52910	24000
C8734	15.0T AirBlock®	8	200	9.537	242	109.04	3089	1	26	33069	15000	66138	30000

Contact Harken to request quote and lead time. For full product line, visit www.harkencustom.com *Max loop Ø: 1/4" (7 mm) **Loops not included