

Cam Cleat Accessories

NEW: 475, 476

Use these accessories to adapt our cleats for many applications, such as cleaning up your cockpit controls with color-coding or leading a line cleanly to a cleat.

Wire fairleads maintain a low profile while holding the line close to the cleat.

The X-Treme Angle Fairlead allows releasing and recleating at angles up to 90° to the cleat. This sets it apart from other fairleads where line uncleats at extreme angles, and can't recleat without centering the line. The low-friction stainless bail provides a bulletproof turning point. Perfect for traveler and cabintop controls or deck cleats—a must for the new Laser® deck cleating system.

Low-profile top-mounted fairleads can also be used to guide lines. They feature stainless wearguards and are available in various colors for color-coding your cams. We offer a wide range of eyestraps to hold line at the cleat and to provide fair leads.



Stainless steel loop provides low-friction turning post

Cleat and uncleat at angles up to 90 degrees

Base plate ensures optimal cleating height

Ideal for Laser® outhaul/cunningham controls

476

Use with risers and angled wedges

475 and 476: available January 2009

Part No.	Description	Height above cam		Height		Length		Width		Weight		Fastener Spacing		Fits
		in	mm	in	mm	in	mm	in	mm	oz	g	in	mm	
Micro														
281	Eyestraps	1/2	12	—	—	17/16	36	7/16	11	.16	4.5	1 1/16	27	468/471
475	Wire fairlead	—	—	15/16	23	1 1/8	48	15/16	24	.29	8	1 1/16	27	468/471
293	Flat cam riser	—	—	5/8	16	1 1/8	48	15/16	24	.50	14	1 1/16	27	468/471
294	15° Angled micro cam riser	—	—	3/4	19	1 1/8	48	15/16	24	.75	21	1 1/16	27	468/471
297	Cam wedge kit	—	—	—	—	1 1/8	48	15/16	24	.16	5	1 1/16	27	468/471
476	X-Treme Angle Fairlead	7/8	22	1 1/16	37	1 5/16	33	2	51	1	29	1 1/16	27	468/471
424	Flairlead‡‡	7/16	11	—	—	1 5/8	41	5/8	16	.13	3.5	1 1/16	27	468/471
Standard														
137	Eyestraps	3/4	19	—	—	2	51	9/16	14	.32	9	1 1/2	38	150/365
145	Cam wedge kit	—	—	—	—	2 9/16	65	1 1/4	32	1.00	28	1 1/2	38	150/365
201	Low-profile eyestraps	3/8	10	—	—	1 1/8	48	7/16	11	.16	4.5	1 1/2	38	150/365
295	Flat cam riser	—	—	1	28	2 9/16	65	1 1/4	32	1.50	38	1 1/2	38	150/365
296	15° Angled cam riser	—	—	1	25	2 9/16	65	1 1/4	32	1.25	35	1 1/2	38	150/365
298	Wire fairlead	—	—	1 1/4	32	2 9/16	65	1 1/4	32	.50	14	1 1/2	38	150/365
375	X-Treme Angle Fairlead‡	15/16	24	2 1/4	57	1 13/16	46	2 9/16	65	1.92	56	1 1/2	38	150
380	X-Treme Angle Fairlead‡	15/16	24	2 9/16	54	1 13/16	46	2 9/16	65	1.92	56	1 1/2	38	365
425	Flairlead‡‡	5/8	16	—	—	2 3/16	56	1 3/16	21	.25	7	1 1/2	38	150/365
431	Colored cam caps‡‡	blue/yellow/green/black/red												150/468/365/471
438	Cam adapter plate	—	—	9/16	14	3	76	1 1/16	36	2.50	71	1 1/2	38	150/365
Offshore														
282	Large eyestraps	15/16	23	—	—	2 13/16	71	3/4	19	.80	23	2 1/16	52	280
283	Offshore cam wedge kit	—	—	—	—	3 3/8	85	1 1/2	38	1.50	43	2 1/16	52	280

‡Max line Ø: 3/8" (10 mm) ‡‡ Indicate color: BL (blue), Y (yellow), G (green), B (black), R (red)