

# Small Boat CB Cars

Small Boat Captive Ball Traveler Cars are used on large dinghies, keelboats, beach cats and offshore boats to 27 ft (8 m). The one-piece solid aluminum construction is lightweight and strong. Ball bearings run on machined aluminum Hardkote-anodized races for smooth trimming and easing. Stainless steel wire guides keep the balls captive when the car is off the track.

Cars with a 500 lb (227 kg) safe working load use Delrin® balls. Cars with a higher safe working load use high-strength Torlon® balls.

Ti-Lite cars matched with Ti-Lite blocks provide the ultimate lightweight, low-profile system. High-tech line replaces shackles and spring.

Consult chart on page 101 to size traveler to mainsail area.

**Use for:**  
Mainsheet Systems  
Genoa Leads

*Blocks attach directly to the toggle for a low-profile, compact system*

*Pivoting shackle and toggle cars have low pivot points to handle non-vertical loads*

*Tough one-piece aluminum construction*

*Captive balls make cars easy to load and maintain. Wire guides circulate bearings smoothly*

*The Radial Traveler car has a curved ball race to fit curved track—perfect for radial vang on boats like the Star*



2730  
2731



**CB Cars only fit Small Boat CB track 2720, 2721, 373, 374, 2725, 2751. Non-captive cars available upon request.**

Part No.	Description	Length		Width		Car body Height		Weight		Maximum working load		Breaking load	
		in	mm	in	mm	in	mm	oz	g	lb	kg	lb	kg
382	1250/Radial/shackle‡	4 1/8	105	2 1/4	57	1 5/16	24	6.24	177	1250	567	2500	1134
2726	Pivoting shackle	2 7/8	73	2 1/4	57	1 5/16	24	4.64	132	500	227	2500	1134
2727	High-load/pivoting shackle	2 7/8	73	2 1/4	57	1 5/16	24	4.64	132	850	386	2500	1134
2728	Fixed sheaves/eyestrapp	2 7/8	73	2 1/4	57	1 5/16	24	5.6	159	500	227	2500	1134
2729	High-load/fixed sheaves/eyestrapp	2 7/8	73	2 1/4	57	1 5/16	24	5.6	159	850	386	2500	1134
2730	Stand-up toggle	2 7/8	73	2 1/4	57	1 5/16	24	5.12	145	500	227	2500	1134
2731	High-load/stand-up toggle	2 7/8	73	2 1/4	57	1 5/16	24	5.12	145	850	386	2500	1134
2732	Ti-Lite	2 7/8	73	2 1/4	57	1 5/16	24	4	113	500	227	2500	1134
2733	High-load/Ti-Lite	2 7/8	73	2 1/4	57	1 5/16	24	4	113	850	386	2500	1134
2734	High-load/fixed sheaves/adjustable cam arms	6 1/4	171	3 1/8	80	1 5/16	24	14.88	422	850	386	2500	1134
2735	1250/Pivoting toggle	4 1/8	105	2 1/4	57	1 5/16	24	6.72	191	1250	567	2500	1134
2736	1250/Fixed sheaves/eyestrapp	4 1/8	105	2 1/4	57	1 5/16	24	7.04	200	1250	567	2500	1134
2737	1250/Pivoting sheaves/eyestrapp	4 1/8	105	2 1/4	57	1 5/16	24	9.6	272	1250	567	2500	1134
2738	1250/Pivoting sheaves/swivel cam	4 1/8	105	6 1/8	156	1 5/16	24	19.84	562	1250	567	2500	1134
2753	Pivoting shackle/control tangs	2 7/8	73	2 1/4	57	1 5/16	24	5.28	150	500	227	2500	1134
2754	High-load/pivoting shackle/control tangs	2 7/8	73	2 1/4	57	1 5/16	24	5.28	150	850	386	2500	1134

See page 26 for replacement balls ‡For horizontal curved track only—24"–40" (600–800 mm) radius