

Aluminum & Stainless Steel T-Track

Anodized aluminum T-Track features rounded top edges for protection and impact resistance. Drilled and tapped holes at ends make endstop and B1877 end control installation easy. Track comes in clear or black-anodized finishes.

32 mm High-Performance Track features black Hardkote-anodizing. It has precise 33 mm pinstop hole spacing.

Stainless steel track is available in 32 and 40 mm. The high luster finish makes it ideal for luxury cruisers/racers from 33 ft to 140 ft (9.5 m to 42 m).



1836
1889



B809
B810



B811

B204
3087
B206

B205
3086
B207

3121

1835

1888

Part No.	Length		Weight		Fasteners (FH)		Pinstop hole spacing		Endstop Part No.
	ft/in	m	oz	kg	in	mm	in	mm	
26 mm Anodized Aluminum: B204 Clear & B205 Black									
B204/B205.1m	3'3 3/8"	1	18.17	0.52	1/4	6	3 19/16	100	B809
B204/B205.1.5m	4'11 1/16"	1.5	27.25	0.77	1/4	6	3 19/16	100	B809
B204/B205.2m	6'6 3/4"	2	36.33	1.03	1/4	6	3 19/16	100	B809
B204B/B205.2.5m	8'2 1/16"	2.5	45.5	1.29	1/4	6	3 19/16	100	B809
B204/B205.3m	9'10 1/8"	3	54.50	1.55	1/4	6	3 19/16	100	B809
B204/B205.6m	19'8 1/4"	6	108.99	3.09	1/4	6	3 19/16	100	B809
32 mm Anodized Aluminum: 3086 Black & 3087 Clear									
3086/3087.1m	3'3 3/8"	1	31.7	0.9	5/16	8	3 19/16	100	B810
3086/3087.1.5m	4'11 1/16"	1.5	45.5	1.29	5/16	8	3 19/16	100	B810
3086/3087.2m	6'6 3/4"	2	63.46	1.8	5/16	8	3 19/16	100	B810
3086/3087.2.5m	8'2 1/16"	2.5	79.32	2.24	5/16	8	3 19/16	100	B810
3086/3087.3m	9'10 1/8"	3	95.22	2.69	5/16	8	3 19/16	100	B810
3086/3087.4m	13'1 1/2"	4	126.98	3.59	5/16	8	3 19/16	100	B810
3086/3087.6m	19'8 1/4"	6	190.5	5.39	5/16	8	3 19/16	100	B810
32 mm High-Performance Hardkote-Anodized Aluminum									
3121.1m	3'3 3/8"	1	30.3	0.86	5/16	8	1 15/16	33	B810
3121.1.2m	3'11 1/16"	1.2	37	1.05	5/16	8	1 15/16	33	B810
3121.1.5m	4'11 1/16"	1.5	45.5	1.29	5/16	8	1 15/16	33	B810
3121.2.5m	8'2 1/16"	2.5	75.3	2.13	5/16	8	1 15/16	33	B810
32 mm Stainless Steel									
1835.2m	6'6 3/4"	2	169.31	4.8	5/16	8	1 15/16	50	1836
1835.4m	13'1 1/2"	4	338.62	9.6	5/16	8	1 15/16	50	1836
40 mm Anodized Aluminum: B206 Clear & B207 Black									
B206/B207.1m	3'3 3/8"	1	48.85	1.39	5/16	8	3 19/16	100	B811
B206/B207.1.8m	5'10"	1.8	87.94	2.49	5/16	8	3 19/16	100	B811
B206/B207.2m	6'6 3/4"	2	97.71	2.77	5/16	8	3 19/16	100	B811
B206/B207.2.5m	8'2 1/16"	2.5	122.13	3.46	5/16	8	3 19/16	100	B811
B206/B207.3m	9'10 1/8"	3	146.56	4.16	5/16	8	3 19/16	100	B811
B206/B207.3.5m	11'5 15/16"	3.5	170.99	4.85	5/16	8	3 19/16	100	B811
B206/B207.4m	13'1 1/2"	4	195.41	5.54	5/16	8	3 19/16	100	B811
B206/B207.6m	19'8 1/4"	6	293.12	8.31	5/16	8	3 19/16	100	B811
40 mm Stainless Steel									
1888.2m	6'6 3/4"	2	282.91	8	—	12	1 15/16	50	1889
1888.4m	13'1 1/2"	4	564.37	16	—	12	1 15/16	50	1889

†1st hole (1 15/16") 40 mm ††1st hole (1 15/16") 50 mm Mounting hole spacing (3 19/16") 100 mm

