

# MKIV Under-Deck Unit 1

Typical Boat Length 28' - 36' (8.3 - 11 m)

| Wire Ø (1 x 19 SS)              | Rod Ø                   | Clevis Pin Ø   |
|---------------------------------|-------------------------|----------------|
| 1/4", 3/32", 5/16" (6, 7, 8 mm) | -8, -10 (5.72, 6.35 mm) | 1/2" (12.7 mm) |

**Headstay Length** Standard 45'11" (13.99 m); max 52'11" (16.12 m)

| Part No.    | Description  |
|-------------|--|
| 7411.11 1/2 | Under-Deck Furling system with 1/2" (12.7 mm) clevis pin |

## Optional Parts

|         |   |
|---------|---|
| 7411.30 | Extra 7' (2.13 m) luff foil extrusion     |
| 7411.31 | Extra 7" (178 mm) connector with bushings |

# MKIV Under-Deck Unit 2

Typical Boat Length 35' - 46' (10.6 - 14.2 m)

| Wire Ø (1 x 19 SS)     | Rod Ø                    | Clevis Pin Ø   |
|------------------------|--------------------------|----------------|
| 5/16", 3/8" (8, 10 mm) | -12, -17 (7.14, 8.38 mm) | 5/8" (15.9 mm) |

**Headstay Length** Standard 60'4" (18.38 m); max 67'4" (20.51 m)

| Part No.    | Description  |
|-------------|--|
| 7412.11 5/8 | Under-Deck Furling system with 5/8" (15.9 mm) clevis pin |

## Optional Parts

|         |   |
|---------|---|
| 7412.30 | Extra 7' (2.13 m) luff foil extrusion     |
| 7412.31 | Extra 9" (229 mm) connector with bushings |

# MKIV Under-Deck Unit 3

Typical Boat Length 45' - 60' (13.7 - 18.3 m)

| Wire Ø (1 x 19 SS)      | Rod Ø                     | Clevis Pin Ø               |
|-------------------------|---------------------------|----------------------------|
| 7/16", 1/2" (11, 12 mm) | -22, -30 (9.53, 11.10 mm) | 3/4", 7/8" (19.1, 22.2 mm) |

**Headstay Length** Standard 75'1" (22.88 m); max 82'1" (25.02 m)

| Part No.    | Description  |
|-------------|--|
| 7413.11 3/4 | Under-Deck Furling system with 3/4" (19.1 mm) clevis pin |
| 7413.11 7/8 | Under-Deck Furling system with 7/8" (22.2 mm) clevis pin |

## Optional Parts

|         |   |
|---------|---|
| 7413.30 | Extra 7' (2.13 m) luff foil extrusion         |
| 7413.31 | Extra 9 3/4" (248 mm) connector with bushings |

## Dimensions

| Unit | Part No.    | A        |        | B       |        | C      |        |        |     |         |     |
|------|-------------|----------|--------|---------|--------|--------|--------|--------|-----|---------|-----|
|      |             | Min in   | Max mm | Min in  | Max mm | Min in | Max mm |        |     |         |     |
| 1    | 7411.11 1/2 | 10 5/8   | 270    | 15 5/8  | 397    | 5 1/2  | 140    | 4 5/8  | 117 | 9 5/8   | 244 |
| 2    | 7412.11 5/8 | 12 11/16 | 322    | 18 9/16 | 471    | 6 5/8  | 167    | 5 5/8  | 137 | 11 5/16 | 287 |
| 3    | 7413.11 3/4 | 16 1/8   | 410    | 23 3/8  | 600    | 8 3/16 | 208    | 6 7/8  | 175 | 14 3/8  | 365 |
| 3    | 7413.11 7/8 | 16 7/16  | 421    | 24 1/4  | 616    | 8 3/16 | 208    | 7 5/16 | 186 | 15      | 381 |



7411.30  
7412.30  
7413.30

7411.31  
7412.31  
7413.31

