

Modern Large Cruising & Megayachts

NEW: B1145TC




B1135ST



B1140ST



B1150ST



Ordering Information:

Specify material by adding letter code to part number. See chart for availability. For underdeck drive add UD to the part number.



Letter Code

1st letter: Base, 2nd letter: Drum, 3rd letter: Top
A Aluminum base, drum and top
GGG* Grey-anodized aluminum base, drum and top
ASA* Aluminum base, stainless drum, aluminum top
SSS* Stainless steel base, drum and top
 *A = Aluminum, G = Grey-anodized aluminum, S = Stainless Steel

Part No.	Material				Gear ratio			Power ratio			Fastener circle		Fasteners (SH)	
	A	GGG	ASA	SSS	1	2	3	1	2	3	in	mm	in	mm
B1111ST	✓	—	—	—	1:1	9.7:1	44.7:1	1.8:1	17.6:1	81.1:1	10 ⁵ / ₁₆	278	8 x 3/8	8 x 10
B1120ST	—	—	✓	✓	2:1	11.4:1	33.3:1	3.4:1	19.3:1	56.3:1	14 ³ / ₈	365	12 x 3/8	12 x 10
B1135ST	—	—	✓	✓	1.1:1	10.8:1	55.2:1	1.6:1	16.9:1	86.5:1	12 ³ / ₄	324	9 x 1/2	9 x 12
B1140ST	—	—	✓	✓	2.9:1	11.6:1	42.6:1	4:1	16.4:1	60.1:1	18 ³ / ₈	460	8 x 1/2	8 x 12
B1145.3TC	✓	✓	—	—	2.9:1	11.9:1	53.6:1	4.1:1	16.6:1	75.6:1	17 ³ / ₄	450	14 x 1/2	14 x 12
B1150ST	—	—	✓	✓	3.4:1	15.3:1	64.9:1	4.2:1	19:1	80.4:1	22 ¹ / ₁₆	560	12 x 1/2	12 x 12

Part No.	Drum (D)		Base (B)		Height (H)		A/GGG		Weight ASA		SSS		Line Ø		Line entry height (LE)			
	in	mm	in	mm	in	mm	lb	kg	lb	kg	lb	kg	in	mm	in	mm		
B1111ST	11 ¹ / ₃₂	280	14 ³ / ₁₆	360	9 ³ / ₃₂	236	50.3	22.8	—	—	—	—	7 ¹ / ₁₆	11	3/4	19	3 ³ / ₃₂	80
B1120ST	11 ¹³ / ₁₆	300	16 ¹³ / ₃₂	418	14 ³ / ₁₆	370	—	—	127.8	58	—	—	9 ³ / ₁₆	14	1	25	6 ¹³ / ₃₂	163
B1135ST	12 ³ / ₄	324	16 ³ / ₃₂	410	12 ¹ / ₈	308	—	—	220.5**	100**	—	—	5/8	16	7/8	22	4 ¹¹ / ₃₂	110
B1140ST	14 ³ / ₁₆	360	22 ¹ / ₈	562	18 ³ / ₁₆	462	—	—	299.9	136	—	—	3/4	19	1 ¹ / ₄	32	8 ¹¹ / ₃₂	212
B1145.3TC	14 ¹ / ₄	362	21 ³ / ₁₆	538	16 ¹ / ₂	419	187.1	84.9	—	—	—	—	3/4	19	1 ¹ / ₄	32	8 ³ / ₁₆	208
B1150ST	16 ⁵ / ₃₂	410	25 ³ / ₁₆	640	19 ³ / ₄	502	—	—	485**	220**	—	—	9/16	14	1	25	8 ²⁷ / ₃₂	225

**Drum is carbon with stainless steel sleeve. Chrome not available
 Carbon fiber available for base, self-tailing arm and top. Availability varies by winch. Contact Harken® for information